

# SD1600P USB-C Mobile 4K Dock with pass-through charging

Part number: K33968EU UPC code: 8589633968

#### SYSTEM REQUIREMENT

· Operating systems supported:

Windows 7, 8.1, 10; macOS 10.13 or later; Chrome OS

· System resource requirement:

Host device must support DisplayPort Alt mode over USB-C

· Ethernet requirement:

Requires a one-time LAN driver download at installation on macOS

#### **HOST CONNECTIVITY**

Host docking connector: USB-C and Thunderbolt 3

#### **VIDEO CONNECTIONS**

· Video connectors:

o HDMI: UHD VGA: FHD

• HDCP support: Yes

· Maximum resolution supported:

HDMI: 3840 x 2160 @30Hz

VGA: 2048 x 1152 @60Hz

## **USB CONNECTIONS**

• All ports: Support up to 5Gbps transfer rate

• USB-C 3.1 Gen 1 ports: One

• USB-A 3.0 ports:Two

#### **NETWORK CONNECTIONS**

• Ethernet port: RJ45

• Compatible Ethernet speeds: 10/100/1000Mbps

#### POWER AND ENVIRONMENTAL

· Bus powered

USB-C power delivery 3.0

5V/9V/20V up to 3A

o 60W Maximum

• Operating temperature: 10 to 40°C (50 to 104°F)

• Storage temperature: -10 to 60° C (-14 to 140° F)

• Relative humidity: 5% to 95% non-condensing

# Kensington

## **PRODUCT DIMENSIONS**

· Unit dimensions without peripherals:

Width: 77.52mm (3.05in) o Depth: 135.52mm (5.33in) Height: 16mm (0.63in)

• Unit weight: 110g (3.88oz)

• Cable length: Tethered cable and up to 205mm (8in)

• Enclosure colour and material: Black PC/ABS

#### PACKAGING DIMENSIONS

• Packaging style: Retail box

· Packaging dimensions:

Width: 135mm (5.31in) o Depth: 200mm (7.87in)

Height: 55mm (2.17in) • Packaging weight: 190g (6.7lbs)

• Master Carton: 5 pcs

Package content:

o One SD1600P Dock

o One Quick Start Instruction Guide

Warranty information

#### COUNTRY OF ORIGIN, REGULATORY, AND WARRANTY

• Country of origin: China

• Certifications and Compliance: CE, FCC, RCM, REACH, RoHS, WEEE, HDMI 1.4 certified

• Warranty: 2-Years limited - worldwide