

SD4842P EQ USB-C® 10Gbps Triple Video Driverless Docking Station

Part Number: K32810NA | UPC Code: 0 85896 32810 0

The sustainable dock for triple screens.

Ideal for professionals requiring a plug-and-play docking solution for USB-C laptops and organizations putting sustainability at the forefront, the SD4842P USB-C® 10Gbps Triple Video Docking Station amplifies visual productivity.

The plastic in this product contains up to 70% post-consumer recycled (PCR) content.*

The SD4842P supports up to 3 external Full HD monitors (1080p @ 120Hz) via 1 x DP and 2 x HDMI® connections. The dock also eliminates the need for cumbersome adapters, charging connected accessories without relying on a host laptop connection

Expand your screens with an effortless dock that will enhance your workflow and amplify your productivity.

Features include:

- Supports up to 3 external displays (1080p @ 120Hz) via DP and HDMI®
- The plastic in this product contains up to 70% post-consumer recycled (PCR) content.*
- Plug-and-play for Thunderbolt™ 4, Thunderbolt™ 3, USB4®, and USB-C® Alt-Mode
- Up to 100W laptop charging using a compact GaN technology power supply unit
- 5 x plug & charge USB ports, Gigabit Ethernet port, and combo audio jack

- Equipped with a compact GaN technology power supply unit, it offers better power efficiency
- Fixed host cable ensures reliable connection and prevents cable theft
- · Up to 10Gbps data transfer speeds
- Accommodates Zero-Footprint Mounting and Kensington Security Lock
- Free Kensington Dockworks™ software
- 3-year limited warranty

*Excludes the cable, power supply or power cords



SD4842P EQ USB-C® 10Gbps Triple Video Driverless Docking Station

Part Number: K32810NA | UPC Code: 0 85896 32810 0

Front



Back



SD4842P EQ USB-C® 10Gbps Triple Video Driverless Docking Station

Part Number: K32810NA | UPC Code: 0 85896 32810 0



Triple Video Displays

The SD4842P supports up to 3 external monitors (1080p @ 120Hz) via one DP and two HDMI® connections.



Sustainability Attributes

The plastic in this product contains up to 70% post-consumer recycled (PCR) content.



Up to 100W Power Delivery

Supports up to 100W laptop charging using GaN technology power supply unit, which is more compact in size and better in power efficiency, and its plug-and-play feature allows continuous charging of connected devices even when the host laptop is unplugged.



Plug-and-Play

A simple plug-and-play solution for Thunderbolt™ 4, Thunderbolt™ 3, USB4®, and USB-C® Alt-Mode laptops running Windows 10 or above. No drivers or downloads required.



Multiple Productivity Ports

5 x plug-and-charge USB ports support peripherals with up to 10Gbps (2 x USB-C® 3.2 Gen2 (5V/3A) and 3 x USB-A 3.2 Gen2 (5V/0.9A)). Also, it includes 1 x Gigabit Ethernet port and 1 x combo audio jack.



Fixed Host Cable and Compact GaN Power Supply

A fixed host cable ensures a reliable connection between the dock and the laptop, providing peace of mind against cable theft. The compact GaN technology power supply unit offers better power efficiency.



Zero-Footprint Mounting Option and Security Cable Lock Slots

Maximize desktop space by mounting your docking station out of the way. Mounting bracket sold separately (K34050WW). Protect your investment with a Kensington cable lock (K65020WW or K65021WW), sold separately. card readers.



Free Kensington DockWorks™ Software and 3-Year Limited Warranty

Free DockWorks™ software delivers the best connection, performance, and security from your Kensington dock. Enjoy peace of mind knowing your covered by Kensington with a professional warranty.

SD4842P EQ USB-C® 10Gbps Triple Video Driverless Docking Station

Part Number: K32810NA | UPC Code: 0 85896 32810 0

	_		
System	Reali	irem	△ntc

	Systems Supported	All Laptops with USB-C port (must support USB-C Alt Mode)
	Operating Systems Supported	Windows® 10 or above
	Plug & Play	Yes
	System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8Gb or above GPU: Intel® HD Graphics 620 or above
	Additional Software Information	DockWorks (Windows® 10 or above)
	USB-C Power Delivery	PD3.0: 5V, 9V, 15V, 20V/5A (Up to 100W fixed powe delivery for laptop charging)
USB Interface		
	Type of USB Connector	Tethered USB-C Host Cable
	Host Connector	Supports Thunderbolt™ 4 / Thunderbolt™ 3 / USB4 / USB-C®
USB Connections		
	Ports	Front Panel : - 2 x USB-C® 3.2 Gen2, 10Gbps (up to 5V/3A) - 1 x USB-A® 3.2 Gen2, 10Gbps (up to 5V/0.9A)
		Back Panel :
		- 2 x USB-A® 3.2 Gen2, 10Gbps (up to 5V/0.9A)
		Side Panel : - 1 x tethered type USB-C® 3.2 Gen2 10Gbps cable (up to 100W Charging)
Network Connections		
	Ethernet Port	RJ45
	Compatible Ethernet Speeds	10/100/1000Mbps
Host Connectivity		
	Host Docking Connector	USB-C tethered type cable with power delivery up to 100W

SD4842P EQ USB-C® 10Gbps Triple Video Driverless Docking Station

Part Number: K32810NA | UPC Code: 0 85896 32810 0

Video Connections

High Resoluti	on		ĠĠĠ
Thunderbolt™ 3/ Thunderbolt™ 4/ USB4®/ USB-C® Alt Mode with DP1.4 HBR3 DSC enabled (Windows)	↓ Up to 8K@30Hz	Up to 4K@60Hz	Up to 4K@30Hz
USB-C® Alt Mode with DP1.4 HBR3 DSC enabled (Windows)	Up to 4K@60Hz	Up to 4K@30Hz	Up to 1080p@60Hz
High Refresh	Rate Hz	Hz Hz	Hz Hz Hz
Thunderbolt™ 3/ Thunderbolt™ 4/ USB4®/ USB-C® Alt Mode with DP1.4 HBR3 DSC enabled (Windows)	↓ Up to 1080p@240Hz	Up to 1080p@120Hz	Up to 1080p@120Hz
	Maximum Resolution Supported	Maximum resolutio Single 8K @ 30Hz Dual 4K @ 60Hz Triple 1080p @ 120	on (DP1.4/HBR3/DSC Enabled) Hz
	HDCP Support	Yes	
Audio Connections			
	Audio Connectors	1 x 3.5mm audio co	mbo jack
	Audio Channels Supported	Stereo LR	
LED Indicator			
	Blue LED	Power indicator	
Material Specifications			
<u> </u>	Exterior and Bottom	The plastic in this procession consumer recycled (*Excludes the cable, power	•
	Product Color	Black	

SD4842P EQ USB-C® 10Gbps Triple Video Driverless Docking Station

Part Number: K32810NA | UPC Code: 0 85896 32810 0

\cap +	har	Feati	ırΔc
()	1121	reall	11 - 5

	Kensington Security Slot	Kensington Security Slot Kensington Nano Security Slot
Product Dimensions		
	Unit Weight	0.64lbs (0.293kg)
	Unit Dimensions without Peripherals	7.68 x 4.09 x 1.42 in (195 x 104 x 36mm)
	Enclosure Color & Material	Black. The plastic in this product contains up to 70% post-consumer recycled (PCR) content.
	Desktop Footprint	25.42in² (164cm²)
Packaging Dimensions		
	Packaging Style	Retail Package (K32810NA)
	Packaging Dimensions	9.65 x 4.33 x 3.94in (245 x 110 x 100mm)
	Packaging Weight	2.54lbs (1.15kg)
	Packaging Content	1 x SD4842P USB-C® Triple Video Docking Station 1 x 149.1W Power Supply Unit 1 x NA Power Cord 1 x Quick Installation Guide 1 x Compliance Sheet 1 x Warranty Card 1 x Welcome Card
	Master Carton	6pcs
Power & Environmental		
	Power Adapter Rating	Input: 100-240V; 2.5A Max Output: 21V DC 7.1A (149.1W)
	Relative Humidity	55% operating temperature @ 77°F (25°C)
	Operating Temperature	32 to 104°F (0 to 40°C)
	Storage Temperature	-0.4 to 140°F (-18 to 60°C)
Country Of Origin, Regu	atory, and Warranty	
	Country of Origin	Vietnam
	Certifications & Compliance	FCC, IC, CE, UKCA, RCM, VCCI, CB, ErP, RoHS, ACCO RS
	Warranty	3-Year Limited - Worldwide



