



SD4840P USB-C 10Gbps Triple Video Driverless Docking Station - 85W PD - DP++/HDMI - Windows

Part Number: K33806NA | UPC Code: 0 85896 33806 2

Expand your productivity.

Expand your productivity with the SD4840P USB-C 10Gbps Triple Video Driverless Docking Station. Features include two DisplayPort++ 1.4 ports, one HDMI 2.0b port; support for a minimum resolution of Single 4K @ 30Hz, Dual 1080p @ 60Hz, and Triple 1080p @ 30Hz when connected to a DP1.2/HBR2 device, and a maximum resolution of Single 5K @ 60Hz, Dual 4K @ 60Hz, and Triple 4K at 30Hz when connected to a DP1.4 HBR3 DSC device; one USB-C 3.2 Gen2 port; three USB-A 3.2 Gen2 ports; a combo audio port; a Gigabit Ethernet port; flexible mounting options; optimized performance with free Kensington DockWorks™ software; and a three-year warranty.

Features include:

- Driverless, USB-C connectivity
- 10Gbps data transfer speed
- Universal Windows compatibility
- Numerous video ports
- Dynamic video support
- 85W Power Delivery (PD 3.0)
- 9-in-1 design with 4 USB-ports
- Flexible mounting options
- Optimize with free Kensington DockWorks™ software
- Three-year warranty



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2021 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. k21-21052p

Kensington

The Professionals' Choice™

SD4840P USB-C 10Gbps Triple Video Driverless Docking Station - 85W PD - DP++/HDMI - Windows

Part Number: K33806NA | UPC Code: 0 85896 33806 2



Driverless USB-C Connectivity

No driver to download, install, or update. 10Gbps data transfer speed and 85W Power Delivery (PD 3.0) make this an ideal solution for all USB-C Windows laptops supporting DisplayPort Alt Mode and Power Delivery.



Universal Windows Compatibility

Connects seamlessly to any laptop running Windows 7 and above.



Numerous Video Ports

With two DisplayPort++ 1.4 ports and one HDMI 2.0b port, select the right connections and resolutions for your needs.



Dynamic Video Support

Supports a minimum resolution of Single 4K @ 30Hz, Dual 1080p @ 60Hz, and Triple 1080p @ 30Hz when connected to a DP1.2/HBR2 device; and a maximum resolution of Single 5K @ 60Hz, Dual 4K @ 60Hz, and Triple 4K @ 30Hz when connected to a DP1.4 HBR3 DSC device.



85W Power Delivery

Quickly and easily charge any Thunderbolt 3, Thunderbolt 4, or USB-C enabled laptop (USB-C laptops must support Power Delivery).



9-in-1 Design with Four USB-ports

The front side features one USB-C 3.2 Gen2 port (up to 5V/1.5A/10Gbps), one USB-A 3.2 Gen2 port (up to BC1.2, 5V/1.5A and Apple Charging, 5V/2.4A/10Gbps), and a combo audio port. The rear features two USB-A 3.2 Gen2 ports (up to 5V/0.9A/10Gbps), a Gigabit Ethernet port, two DP++ 1.4 ports, and one HDMI 2.0b port.



Flexible Mounting Options

Can be set up vertically or horizontally.



Free Kensington DockWorks™ Software and Three-Year Warranty

Optimize your docking station's performance with free Kensington DockWorks™ software. A three-year warranty means you can rest assured knowing you're covered by Kensington.

SD4840P USB-C 10Gbps Triple Video Driverless Docking Station - 85W PD - DP++/HDMI - Windows

Part Number: K33806NA | UPC Code: 0 85896 33806 2

System Requirements

Systems Supported	All Laptops with USB-C port (must support USB-C Alt mode)
Operating Systems Supported	Windows® 7 or above
Plug & Play	Yes
System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8GB or above GPU: Intel® HD Graphics 620 or above
Additional Software Information	DockWorks (Windows 10, macOS 10.15+)
USB-C Power Delivery	PD3.0, 5V/ 9V/ 15V/ 20V@4.25A (up to 85W)

USB Interface

Type of USB Connector	USB-C Connector
Host Connector	Support USB3.2 Gen2 Type-C with USB-C Alt mode

USB Connections

Ports	<p>Front Panel :</p> <ul style="list-style-type: none"> 1 x Power Button 1 x Audio Combo Jack 1 x USB-C 3.2 Gen2 (up to 5V/1.5A) 1 x USB-A 3.2 Gen2 (up to BC1.2, 5V/1.5A and Apple Charging, 5V/2.4A) <p>Back Panel :</p> <ul style="list-style-type: none"> 1 x USB-C Host Port (up to 85W Charging) 2 x DP1.4++ 1 x HDMI 2.0b 1 x 1Gbps Ethernet 2 x USB-A 3.2 Gen2 (up to 5V/0.9A)
-------	---

Network Connections

Ethernet Port	RJ45
Compatible Ethernet Speeds	10/100/1000 Mbps

Host Connectivity

Host Docking Connector	USB-C with Power Delivery up to 85W
------------------------	-------------------------------------

SD4840P USB-C 10Gbps Triple Video Driverless Docking Station - 85W PD - DP++/HDMI - Windows

Part Number: K33806NA | UPC Code: 0 85896 33806 2

Video Connections

Video Connectors	2 x DisplayPort v1.4 ++ 1 x HDMI v2.0b
Maximum Resolution Supported	<p>Minimum Resolution (DP1.2/HBR2): Single 4K@30Hz Dual 1080p@60Hz Triple 1080p@30Hz</p> <p>Maximum Resolution (DP1.4/HBR3 DSC): Single 5K@60Hz Dual 4K@60Hz Triple 4K@30Hz</p>

Audio Connections

Audio Connectors	1 x 3.5mm audio combo jack
Audio Channels Supported	Stereo LR

LED Indicator

Blue LED	Power indicator
----------	-----------------

Material Specifications

Exterior	Enclosure: PC + ABS with texture
Bottom	Metal Base Plate: Sheetmetal
Product Color	PMS Black

Other Features

Kensington Security Slot	Kensington Security Slot
--------------------------	--------------------------

Product Dimensions

Unit Weight	14.10oz (0.4kg)
Unit Dimensions without Peripherals	7.48 x 3.34 x 1.06in (190 x 85 x 27mm)
Enclosure Color & Material	PMS Black, PC ABS
Desktop Footprint	25.11in ² (162cm ²)

SD4840P USB-C 10Gbps Triple Video Driverless Docking Station - 85W PD - DP++/HDMI - Windows

Part Number: K33806NA | UPC Code: 0 85896 33806 2

Packaging Dimensions

Packaging Style	Bulk Package (K33806 EU) Retail Package (K33806 NA/AP/JP)
Packaging Dimensions	11.61 x 5.70 x 3.54in (295 x 145 x 90mm)
Packaging Weight	51.14oz (1.45kg)
Packaging Content	1 x SD4840P Dock 1 x 1M USB-C cable 1 x Power Supply Unit (Power Cord is varied by different SKUs) 1 x Docking Station Stand 1 x IG (Instruction Guide) 1 x Warranty Card 1 x Compliance Sheet 1 x Welcome card insert
Master Carton	4

Power & Environmental

Power Adapter Rating	Input: 100-240V; 1.8A Output: 20V DC 6.75A (135W)
Relative Humidity	55% operating temperature @ 77° F (25°C)
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-22 to 149°F (-30 to 65°C)

Country of Origin, Regulatory, & Warranty

Country of Origin	China for EU/AP/JP, Taiwan for NA
Certifications & Compliance	FCC, IC, CE, RCM, VCCI, UKCA, CB, RoHS, ACCO RSL
Warranty	3-Year Limited - worldwide



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2021 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. k21-21052p

Kensington

The Professionals' Choice™