



# Kensington®

## SD4780P USB-C™ & USB 3.0 Dual 4K Docking Station with 100W Power Delivery

Part Number: K33620EU | EAN Code: 5028252617888

The Ultimate  
USB-C™ & USB  
3.0 Dock for  
Dual 4K Video  
@ 60Hz with  
100W Power  
Delivery.

Features include the ability to select between HDMI 2.0 and DP 1.2 ++, with four video ports in all (no need for cumbersome adapters); six USB ports (front: 1x USB-C 3.1 Gen2 up to 5V/3A and 1x USB-A 3.1 Gen2 up to 5V/2.4A, back: 4x USB-A 3.1 Gen1 up to 5V/0.9A); 100W of Power Delivery (perfect for the newer MacBook Pro); a 1m USB-C to USB-C cable with USB 3.0 adapter (for USB 3.0 devices that require Power Delivery - see our optional power splitter K38310EU); Thunderbolt™ 3 compatibility and Kensington DockWorks™ software for the best connection, performance and security from your Kensington dock. VESA® 75/100 compatible.

Features include:

- Ultra High Definition video for up to two 4K monitors @ 60Hz
- 10Gbps throughput for maximum efficiency
- Flexibility to select between HDMI 2.0 and DP 1.2 ++ ports — choose the best port for your environment
- Support for USB-C and USB 3.0 (A) laptops
- Windows, macOS and Chrome OS compatibility
- 100W Power Delivery
- Six USB ports (two with charging)
- 1m USB-C to USB-C cable with USB 3.0 adapter included (for USB 3.0 (A) devices that require PD, see our optional power splitter K38310EU, sold separately)
- Free DockWorks™ software
- Three-year warranty
- True universal compatibility



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2020 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. CBT30209EN

FOR MORE INFORMATION CONTACT: [contact@kensington.com](mailto:contact@kensington.com)

**Kensington**  
The Professionals' Choice™

## SD4780P USB-C™ & USB 3.0 Dual 4K Docking Station with 100W Power Delivery

Part Number: K33620EU | EAN Code: 5028252617888



### Dual 4K (@60Hz) video output (HDMI 2.0 & DP1.2++)

Delivers Ultra High Definition (4096 x 2160) images. Four video ports allow users the ability to select between HDMI 2.0 and DP 1.2 ++ without the need for cumbersome adapters.

### Universal Hybrid Docking

The SD4780P connects to any USB-C™ or USB 3.0 (A) laptop, is Thunderbolt™ 3 compatible and supports Windows, Mac and Chrome operating systems.

### 100W Power Delivery

Ideal for devices that require higher power, such as the newer MacBook Pro. For USB 3.0 laptops requiring power delivery, see our optional 60W Power Splitter (K38310EU), sold separately.



### Six USB Ports (USB-C and USB 3.0)

Two-layer hub delivers speeds up to 10Gbps. Front: 1x USB-C 3.1 Gen2 up to 5V/3A and 1x USB-A 3.1 Gen2 up to 5V/2.4A; Back: 4x USB-A 3.1 Gen1 up to 5V/0.9A.

### Zero Footprint Mounting Option

Adjustable clamp easily attaches to a desktop edge, cubicle wall, monitor arm, or other surface for maximum mounting flexibility (K34050, sold separately).



### Free Kensington DockWorks™ Software

Enables the best connection, performance, and security from your Kensington dock.



### Three-Year Warranty

Rest assured knowing you're covered by Kensington.

## SD4780P USB-C™ & USB 3.0 Dual 4K Docking Station with 100W Power Delivery

Part Number: K33620EU | EAN Code: 5028252617888

### System Requirements

Systems Supported	All Laptops with USB-C or USB 3.0 ports
Operating Systems Supported	Windows® 10/ macOS 10.15+/ Chrome OS 44+
Plug & Play	DisplayLink Driver needed
Software	Download from DisplayLink website ( <a href="https://www.displaylink.com/downloads">https://www.displaylink.com/downloads</a> )
System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8GB or above GPU: Intel® HD Graphics 620 or above
Additional Software Information	DockWorks (Windows 10, macOS 10.15+)
USB-C Power Delivery	5V/ 9V/ 12V/ 15V/ 20V @ 3A (up to 100W, 20V@5A)

### USB Interface

Type of USB Connector	USB-C & USB 3.0 Connector
Host Connector	Support USB3.1 Gen1 Type A & Type-C

### USB Connections

Ports (Front)	1 x USB3.1 Gen1 Type A, support BC1.2 (5V/1.5A) & Apple Charging (5V/2.4A) 1 x USB3.1 Gen1 Type C (5V/3A, 9V/2A)
Ports (Back)	4 x USB3.1 Gen1 Type A (5V/0.9A)

### Network Connections

Ethernet Port	RJ45
Compatible Ethernet Speeds	10/100/1000 Mbps

### Host Connectivity

Host Docking Connector	USB-C with Power Delivery up to 100W, For USB 3.0 laptops requiring power delivery, see our optional 60W Power Splitter (K38310EU).
------------------------	-------------------------------------------------------------------------------------------------------------------------------------------

### Video Connections

Video Connectors	2 x DisplayPort ++ v1.2 2 x HDMI v2.0
Maximum Resolution Supported	Single Monitor: 4096 x 2160 @ 60Hz Dual Monitors: 4096 x 2160 @ 60Hz

### Audio Connections

Audio Connectors	1 x 3.5mm audio combo jack
Audio Channels Supported	Stereo LR

### LED Indicator

Blue LED	Power indicator
----------	-----------------

## SD4780P USB-C™ & USB 3.0 Dual 4K Docking Station with 100W Power Delivery

Part Number: K33620EU | EAN Code: 5028252617888

### Material Specifications

Exterior	Enclosure: PC ABS with texture
Bottom	Metal Base Plate: Sheet Metal
Product Colour	PMS Black

### Other Features

Kensington Security Slot	Kensington Security Slot / Nano Slot
VESA® Mount Compatible	Yes

### Product Dimensions

Unit Weight	0.385kg (13.58oz)
Unit Dimensions without Peripherals	Width: 210mm (8.26") Depth: 90mm (3.54") Height: 31.3mm (1.23")
Enclosure Colour & Material	PMS Black, PC ABS
Desktop Footprint	189cm <sup>2</sup> (29.29sq.in)

### Packaging Dimensions

Packaging Style	Bulk Packaging
Packaging Dimensions	Width: 235mm (9.25") Depth: 149mm (5.86") Height: 91mm (3.58")
Packaging Weight	1.396kg (3.07lbs)
Packaging Content	1 x SD4780P Dock 1 x USB-C to USB-C cable with USB-A tethered adapter 1 x Power Supply 1 x IG (Instruction Guide) 1 x Warranty Card 1 x Compliance Sheet
Master Carton	4

### Power and Environmental

Power Adapter Rating	Input: 100-240V; 1.8A / Output: 20V DC 8.5A (170W)
Relative Humidity	55% operating temperature @ 25°C
Operating Temperature	0 to 40°C (32 to 104°F)
Storage Temperature	-18 to 60°C (-0.4 to 140°F)

### Country of Origin, Regulatory, and Warranty

Country of Origin	Thailand
Certifications & Compliance	FCC, IC, CE, RCM, VCCI, CB, RoHS, ACCO RSL
Warranty	3-Year Limited - worldwide



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2020 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. CBT30209EN

# Kensington

The Professionals' Choice™