



## SD4760P USB-C® Triple Display Docking Station

Part Number: K33622NA | UPC code: 0 85896 33622 8

Unlock your  
productivity with  
triple displays.

Many IT professionals face the challenge of managing different docks for various laptops, missing the benefits of a unified solution that can support multiple external monitors. The SD4760P USB-C® Triple Display Hybrid Dock addresses these issues by supporting Thunderbolt™ 5, Thunderbolt™ 4, USB4®, USB-C® laptops, and MacBook M1/M2/M3/M4 laptops, enabling up to three external monitors while delivering 100W Power Delivery and universal compatibility across Windows, Chrome, and macOS operating systems. This powerful dock empowers users to enhance their workflows and streamline IT management with one versatile device.

- Up to triple displays for USB-C® laptops and MacBook M1/M2/M3/M4 using DisplayLink®
- Thunderbolt™ 5, Thunderbolt™ 4, USB4®, and USB-C® laptops
- Windows 10 or above, Chrome OS 114 or above, and macOS 11 or above
- Up to 100W laptop charging
- 11-in-1 design with 6 USB-A ports
- Zero-footprint mounting option
- Security cable lock slots
- Delivered in FSC® certified packaging
- Free Kensington DockWorks™ software (Windows only)
- 3-year limited warranty

## SD4760P USB-C® Triple Display Docking Station

Part Number: K33622NA | UPC code: 0 85896 33622 8

Front



2 x USB-A 3.2  
Gen1, 5Gbps  
(up to 5V/0.9A)

3.5mm Audio  
Combo Jack

Back



DC 20V In

USB-C Host Port  
(up to 100W PD)

1 x HDMI 1.4  
(USB-C Alt Mode)

2 x HDMI 1.3



Ethernet  
10/100/1000 Mbps

4 x USB-A 3.2  
Gen1, 5Gbps  
(up to 5V/0.9A)


## SD4760P USB-C® Triple Display Docking Station

Part Number: K33622NA | UPC code: 0 85896 33622 8



### Up to Triple Displays for Windows, Chrome, and macOS Laptops

Universally supports up to three external monitors through a single connection: one 4K display at 30Hz and two 1080p displays at 60Hz using DisplayLink® technology. Supports USB-C® Alt Mode laptops, including MacBook M1, M2, M3, and M4 models.



### Universal Compatibility

Supports Thunderbolt™ 5, Thunderbolt™ 4, USB4®, and USB-C® laptops running Windows 10 or above, Chrome OS 114 or above, and macOS 11 or above.



### Up to 100W Power Delivery

Supports up to 100W laptop charging. KonstantCharge™ enables connected devices to charge even when your host device is undocked.



### 11-in-1 Design

Supports host laptop with 3x HDMI® video ports, 6x USB-A 3.2 Gen1 5Gbps (5V/0.9A) ports, 1x combo audio jack, and a Gigabit Ethernet port.\*



### Zero-Footprint Mounting Option & Security Cable Slots

Maximize desktop space by mounting your docking station out of the way. Mounting bracket sold separately (K34050WW). Protect your investment with a Kensington cable lock (K65020WW or K65021WW), sold separately.



### Kensington DockWorks™ Software

Free DockWorks™ software (Windows only) delivers the best connection, performance, and security from your Kensington dock.



### Sustainability Attributes

As part of our efforts to reduce our environmental impact, this docking station is delivered in Forest Stewardship Council (FSC®) certified packaging.

\*This dock supports the Gigabit Ethernet standard which provides a maximum data rate of 1Gbps. Actual Ethernet speeds may vary depending on, but not limited to, Internet bandwidth, Ethernet cables, network switches, and the hardware and firmware performance of the host computer.

# SD4760P USB-C® Triple Display Docking Station

Part Number: K33622NA | UPC code: 0 85896 33622 8

## System Requirements

Systems Supported	Laptops with USB-C® port (must support USB-C® Alt Mode)
Operating Systems Supported	Windows 10 or above; macOS 11 or above; Chrome OS 114 or above
Plug & Play	No, downloading the latest DisplayLink® driver is required All Chromebooks using ChromeOS build R51 or later will work with DisplayLink® docks and adapters without additional driver installation
Software	Download from the <a href="#">Synaptics DisplayLink® website</a>
Additional Software Information	Compatible with DockWorks™ (Windows only)
System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8Gb or above GPU: Intel® HD Graphics 620 or above
USB-C® Power Delivery	PD3.0: 5V, 9V, 12V, 15V/3A & 20V/5A (up to 100W)

## USB Interface

Type of USB Connector	USB-C®
Host Connector	USB 3.2 Gen1 Type-C with USB-C® Alt Mode

## USB, Video, and Ethernet Connections

Ports	6 x USB-A 3.2 Gen 1, 5Gbps (up to 5V/0.9A, 4.5W) 1 x USB-C® Host Port (up to 100W PD) 2 x HDMI® 1.3 (DisplayLink®) 1 x HDMI® 1.4 (USB-C® Alt Mode) 1 x Ethernet, 10/100/1000Mbps 1 x 3.5mm Combo Audio
-------	---

## Network Connections

Ethernet Port	RJ45
Compatible Ethernet Speeds	10/100/1000Mbps

## Host Connectivity

Host Docking Connector	USB-C® with Power Delivery up to 100W
------------------------	---------------------------------------





## Video Connections

Video Connectors	2 x HDMI® 1.3 (DisplayLink®) 1 x HDMI® 1.4 (USB-C® Alt Mode)
Maximum Resolution Supported	Single: Up to 1 x 4K (3840x2160) @ 30Hz via USB-C® Alt Mode or 1 x 1080p @ 60Hz via DisplayLink® Dual: Up to 1 x 4K (3840x2160) @ 30Hz & 1 x 1080p @ 60Hz Triple: Up to 1 x 4K (3840x2160) @ 30Hz & 2 x 1080p @ 60Hz

## SD4760P USB-C® Triple Display Docking Station

Part Number: K33622NA | UPC code: 0 85896 33622 8

Resolution Table

			
<b>Thunderbolt™ 3 or 4, USB4®, or USB-C® Alt Mode® (Windows)</b>	Up to 4K @ 30Hz	Up to one 4K @ 30Hz + one 1080p @ 60Hz	one 4K @ 30Hz + two 1080p @ 60Hz
<b>MacBook models with M1, M2, M3, or M4 chipsets* (macOS)</b>	Up to 4K @ 30Hz	Up to one 4K @ 30Hz + one 1080p @ 60Hz	one 4K @ 30Hz + two 1080p @ 60Hz
<b>USB-C® devices that do not support Alt Mode</b>	1080p @ 60Hz	1080p @ 60Hz	X

\*This USB-C® dock is compatible with Thunderbolt™ 3, Thunderbolt™ 4, and USB4® laptops; however, it operates at a bandwidth of up to 5Gbps.

Audio Connections	HDCP Support	Supports HDCP 1.4 & 2.3
	Audio Connectors	3.5mm audio jack for headphones/speakers
Material Specifications	Audio Channels Supported	Stereo L/R
	Exterior	PC/ABS with texture
Other Features	Product Color	Black
	Security Slot	Kensington Security Slot Kensington Nano Security Slot
Product Dimensions	Mounting Option	Yes, mounting bracket (K34050WW) sold separately
	Unit Weight	400 x 350 x 430mm (15.7 x 13.7 x 16.9in)
	Unit without Peripherals	200 x 65 x 32mm (7.87 x 3.35 x 1.26in)
	Cable	Diameter: 5mm (0.2in) Length: 1.8m (6ft)
Packaging Dimensions	Desktop Footprint	170cm2 (26.35in2)
	Packaging Style	FSC® certified brown box
	Packaging Dimensions	232 x 144 x 85mm (9.21 x 5.67 x 3.35in)
	Packaging Weight	0.90kg (1.98lbs)

## SD4760P USB-C® Triple Display Docking Station

Part Number: K33622NA | UPC code: 0 85896 33622 8

Packaging Content	1 × SD4760P
	1 × USB-C® Host Cable
	1 × 135W Power Supply Unit
	1 × NA Power Cord
	1 × Quick Installation Guide
	1 × Compliance Sheet
	1 × Warranty Card
Master Carton	8pcs
Power & Environmental	
Power Adapter Rating	Input: 100-240V; 2A
	Output: 20V DC 6.75A (135W)
Relative Humidity	0 to 85% operating temperature @ 25°C (77°F)
Operating Temperature	0 to 45°C (32 to 113°F)
Storage Temperature	-25 to 70°C (-13 to 158°F)
Country of Origin, Regulatory, and Warranty	
Country of Origin	China
Certifications & Compliance	FCC, CE, UKCA, RCM, CB, VCCI, RoHS, ACCO RSL
Warranty	3-Year Limited



All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2025 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. k24-24118p