

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

Part Number: K35234EU | EAN Code: 5028252650861

More screens, more speed, more possibilities. IT professionals working in mixed technology environments often require versatile docking solutions to optimise productivity. For users who need to manage multiple tasks simultaneously such as software developers, graphic designers or data analysts, having the capability to connect up to four external displays is essential.

The SD5920T EQThunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology is designed to meet these needs, providing a seamless connection for both Thunderbolt™ and USB-C® devices.

This high-speed dock supports stunning Quad 4K video output across Windows, macOS and ChromeOS and enhances workflow efficiency by allowing users to multitask effortlessly.

- Up to Quad 4K Video via HDMI®, DP and Thunderbolt™
- Supports Thunderbolt™ 4, Thunderbolt™ 3, USB4® and USB-C® devices
- · Windows, macOS and ChromeOS compatible
- Composed of 100% post-consumer recycled (PCR) aluminium*
- Data transfer speeds up to 40Gbps
- · Daisy chain support
- Intel VT-d DMA protection
- Up to 100W Charging (96W certified)
- · Productive 16-in-1 design
- · Security cable lock slots
- 3-Year limited warranty




^{*} The outer casing of the docking station is made of aluminium.

The PCBA and any related inner components are not made of aluminium.


SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

Part Number: K35234EU | EAN Code: 5028252650861

Front



Back



SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology


Part Number: K35234EU | EAN Code: 5028252650861



Quad 4K Video Output

Supports up to Quad 4K @ 60Hz for Thunderbolt™ 4 devices via plug-and-play TB4 port and MacBook* models with M1/M2/M3/M4 Pro and Max chipsets via DisplayLink®. Provides flexible video connections (HDMI®, DP and TB4) without the need for cumbersome adapters.

*For MacBook models with the M4 base chipset and M1, M2 and M3 Pro or Max chipsets when the laptop lid is open (and M3 base chipset when the laptop lid is closed), this dock supports up to quad 4K @ 60Hz. It also supports up to triple 4K @ 60Hz for M1/M2 base chipsets.



Universal Compatibility

A quick and powerful solution for Thunderbolt™ 4, Thunderbolt™ 3, USB4® and USB-C® devices running Windows (10 or later), macOS (11 or later) and ChromeOS (114 or later).



Recycled Materials

The SD5920T is composed of 100% post-consumer recycled (PCR) aluminium** and is delivered in Forest Stewardship Council (FSC®) certified packaging.

** The outer casing of the docking station is made of aluminium.

The PCBA and any related inner components are not made of aluminium.



Thunderbolt™ 4 Hybrid Technology

Transfers up to 40Gbps of data, video and audio. Provides daisy chain support for SSDs, monitors and other Thunderbolt™ devices. Blocks peripheral devices from unauthorised access to system memory using Intel VT-d DMA protection.

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

Part Number: K35234EU | EAN Code: 5028252650861



Up to 100W Charging (96W certified)

Charges any Thunderbolt™ 4, Thunderbolt™ 3, USB4® or USB-C® laptop, while also providing power to any connected USB-C® or USB4® accessories, including phones, tablets and watches. KonstantCharge™ allows connected devices to charge even when your host device is undocked.



Productive 16-in-1 Design

16 ports deliver expanded connectivity options.

2 x Thunderbolt™ 4 downstream ports capable of data, video, and audio

1 x Thunderbolt™ host port

1 x USB-C[®] 3.2 Gen2 10Gbps

1 x USB-A 3.2 Gen2 10Gbps

2 x USB-A 3.2 Gen1 5Gbps

2 x HDMI®/DP

1 x DP

1 x 3.5mm combo audio jack

1 x SD Card reader

1 x Micro SD Card reader

1 x 2.5Gbps Ethernet



Security Cable Lock Slots

Protect your investment with a Kensington cable lock (K65020EU or K65021WW), sold separately.



3-Year Limited Warranty

Enjoy peace of mind knowing you are covered by Kensington with a professional warranty.

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

System Requirements


	Systems Supported	Thunderbolt™ 4, Thunderbolt™ 3 and USB4 devices		
		running Windows 11 or above, macOS 14 or above of ChromeOS 114 or above.		
	Operating Systems Supported	Windows 11 or above, macOS 14 or above or ChromeOS 114 or above.		
	Plug & Play	For video options 3, 4 and 5, up to two displays are supported as plug-and-play.		
	Software	Please download the latest DisplayLink driver for video options 1 and 2		
	System Resource Requirement	CPU: Apple M1/M2/M3/M4 chip (Base, Pro, Max), or Intel® Core™ i5 6th generation or above Memory: 8Gb or above GPU: Intel® HD Graphics 620 or above		
	USB-C Power Delivery	PD 3.0: 5V, 9V, 15V, 20V/4.8A, up to 100W charging (96W certified)		
USB Interface				
	Type of USB Connector	Thunderbolt™ 4		
	Host Connector	Thunderbolt™ 4 / USB4 / USB-C®		
USB Connections				
	Ports	Front Panel: • 1 x Thunderbolt™ 4 Downstream Facing Port, 40Gbps (up to 5V/3A, 15W) • 1 x USB-C® 3.2 Gen2, 10Gbps (up to 5V/3A, 15W) • 1 x USB-A 3.2 Gen2, 10Gbps (up to 5V/1.5A, 7.5W) • 1 x SD Card Reader & 1 x Micro SD Card Reader (UHS-II, SD4.0) • 1 x 3.5mm Audio Combo Jack • 1 x Power Button with Power LED indicator		
		Rear Panel: • 2 x USB-A 3.2 Gen1, 5Gbps (up to 5V/0.9A, 4.5W) • 1 x Thunderbolt™ 4 Host Port, 40Gbps (up to 96W charging) • 1 x Thunderbolt™ 4 DFP, 40Gbps (up to 5V/3A) • 2 x HDMI (4K @ 60Hz) • 2 x DP (4K @ 60Hz) • 1 x DP (up to 8K @ 60Hz) • 1 x DC input • 1 x Ethernet port 10/100/1000/2500Mbps		

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

Ν	et	٦٨	/	rl	/	$\overline{}$	\cap	n	n	ρ,	-+	in	ns


——————————————————————————————————————				
	Ethernet Port	RJ45		
	Compatible Ethernet Speeds	10/100/1000/2500Mbps		
Host Connectivity				
	Host Docking Connector	1 x Thunderbolt™ 4 Host Port, 40Gbps (up to 96W charging)		
Video Connections				
	Video Connectors			
	Video 1: Video 2:	1 x HDMI / DP (4K @ 60Hz) 1 x HDMI / DP (4K @ 60Hz)		
	Video 3:	1 x DP (Up to 8K @ 60Hz)		
	Video 4:	1 x Thunderbolt™ 4 DFP, 40Gbps (up to 5V/3A)		
	Video 5:	1 x Thunderbolt™ 4 DFP, 40Gbps (up to 5V/3A)		
	Maximum Resolution Supported			
	Quad Monitors:	Up to 4K @ 60Hz each		
	Triple Monitors:	Up to one at 8K @ 60Hz and two at 4K @ 60Hz each		
	Dual Monitors:	Up to one at 8K @ 60Hz, and one at 4K @ 60Hz		
	Single Monitor:	Up to 8K @ 60Hz via Thunderbolt™ port		
	For details, please refer to the follo	owing resolution table.		
	HDCP Support			
	Video 3, 4, 5:	Yes		
	Video 1, 2:	No		

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology




Video counts	Technology Note I/O conne		I/O connection	Video resolution
	DisplayLink®	Driver installation required	1 + 2	Up to 2 x 4K @ 60Hz
	Thunderbolt™	Plug and play	3 + 4	Thunderbolt™ laptop (Windows) 1 x 8K @ 60Hz + 1 x 4K @ 60Hz
			4 + 5	MacBook Pro and Max chipsets (macOS)
			5 + 3	Up to 2 x 6K @ 60Hz (5K+6K for M3 base chipset lid closed)

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology



Video counts	Technology	Note	I/O connection	Video resolution
	DisplayLink®	Driver installation required	1 + 2	Up to 2 x 4K @ 60Hz
			3	Thunderbolt™ laptop (Windows) 1 x 8K @ 60Hz
	Thunderbolt™	Plug and play	4	USB-C® Alt Mode laptop(Windows) 1 x 4K @ 60Hz
			6	MacBook M series base chipsets(macOS) Up to 1 x 6K @ 60Hz

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology



SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

Λ	dia	Con	nect	ionc
ALL		(() I	irie (i	1()115

Audio Connections		
	Audio Connectors	1 x 3.5mm audio combo jack
	Audio Channels Supported	Stereo LR
LED Indicator		
	Blue LED	Power on (host connected)
	Orange LED	Power on (host disconnected)
Material Specifications		
	Exterior	Main body outer casing: 100% PCR Aluminium
	Bottom	Main body bottom casing: 73% PCR Plastic
	Product Colour	Black
Other Features		
	Kensington Security Slot	Kensington Security Slot Kensington Nano Security Slot
Product Dimensions		
	Unit Weight	0.6kg (1.32lbs)
	Unit Dimensions without Peripherals	225 x 85 x 22mm (8.86 x 3.35 x 0.87")
	Enclosure Colour & Material	Black, 100% PCR Aluminium & 73% PCR PC+ABS
	Desktop Footprint	191.22cm ² (29.68in ²)
Packaging Dimensions		
	Packaging Style	Retail Package (K35234EU)
	Packaging Dimensions	242 x 108 x 100mm (9.53 x 4.25 x 3.94")
	Packaging Weight	1.19kg (2.62lbs)
	Packaging Content	1 x SD5920T 1 x 1m (3.28') Thunderbolt™ 4 Certified Passive cable 1 x 149.1W Power Supply Unit 1 x EU Power Cord 1 x UK Power Cord 1 x Quick Installation Guide 1 x Compliance Sheet 1 x Warranty Card 1 x Welcome Card
	Master Carton	6pcs

SD5920T EQ Thunderbolt™ 4 Quad 4K Hybrid Dock with DisplayLink® Technology

Part Number: K35234EU | EAN Code: 5028252650861

Warranty

		menta	

	Power Adapter Rating	Input: 100-240V; 2.5A max. Output: 21V DC 7.1A (149.1W)		
	Relative Humidity	55% operating temperature @ 25°C (77°F)		
	Operating Temperature	0 to 40°C (32 to 104°F) -18 to 60°C (-0.4 to 140°F)		
	Storage Temperature			
Country Of Origin,	Regulatory, and Warranty			
	Country of Origin	Vietnam		
	Certifications & Compliance	FCC, IC, CE, UKCA, RCM, ErP, CB, RoHS, ACCO RSL, UK, PSTI		

3-Year Limited - Worldwide



